



Most Trusted Traveling Irrigation Systems
Since 1964

Caprari Model D1/50 PTO Pump



Fully-Fitted D2/50 Pictured

- Compact, reliable PTO pump capable of 50 to 330 gpm with corresponding pressures of 90 to 70 psi using 8.5 to 20 hp
- Available with heavy duty two wheeled trailer or galvanized three point mount
- Designed with industry leading oil lubricated step up gearbox (no belts or pulleys) with shafts supported by widely spaced bearings
- Easily replaceable packing gland type water seal
- Pumps can be fitted with 2" female thread discharge priming valve, hand primer, fluid filled pressure gauge, short suction adapter with 3" female pipe thread and #6 heavy duty 1 3/8 six spline PTO shaft

Technical Specifications


Discharge & Suction	(Bare or Pump, Cart & Shaft) Flanged
Discharge & Suction	(Fully Fitted) 2" NPT (F) Discharge, 3" NPT (F) Suction
Discharge Position	Horizontal, Right Facing (When Standing Behind The Suction End)
Length	62 Inches
Width	48 Inches
Height	36 Inches
Weight (Unfitted)	200 lbs.
Weight (Fitted)	220 lbs.

Configurations

Bare Pump	Pump only with weld-on companion flanges, gaskets, nuts & bolts
Pump, Cart & Shaft	Same as bare pump, but mounted on two-wheeled cart with PTO drive shaft
Fully Fitted	Same as pump, cart & shaft plus hand primer, check valve, pressure gauge and suction fittings

Options (Additional Fees Apply)

Three-Point Hitch	Fully galvanized frame may be substituted for cart
Suction Hose	3" x 30' Aquaflex
Foot Valves & Strainers	3" Cast or Aluminum 45°
Special Execution	Consult Factory



PTO Input - 540 RPM

GPM	50	100	200	300	330
PSI	90	91	87	75	70
HP	8.5	10	15	19	20

www.kifco.com



Water-Reels®
B-Series Ag-Rain®
Specialty
Pumps

700 S. Schrader Ave.
P.O. Box 290
Havana, IL 62644
800-452-7017 Toll Free
309-543-4425 Phone
309-543-4945 Fax
www.kifco.com